

PSQL Quick Reference

General

`\copyright` show PostgreSQL usage and distribution terms
`\g [FILE] or ;` execute query (and send results to file or |pipe)
`\h [NAME]` help on syntax of SQL commands, * for all commands
`\q` quit psql

Query Buffer

`\e [FILE]` edit the query buffer (or file) with external editor
`\ef [FUNCNAME]` edit function definition with external editor
`\p` show the contents of the query buffer
`\r` reset (clear) the query buffer
`\s [FILE]` display history or save it to file
`\w FILE` write query buffer to file

Input/Output

`\copy ...` perform SQL COPY with data stream to the client host
`\echo [STRING]` write string to standard output
`\i FILE` execute commands from file
`\o [FILE]` send all query results to file or |pipe
`\qecho [STRING]` write string to query output stream (see `\o`)

Formatting

`\a` toggle between unaligned and aligned output mode
`\C [STRING]` set table title, or unset if none
`\f [STRING]` show or set field separator for unaligned query output
`\H` toggle HTML output mode
`\pset NAME [VALUE]` set table output option (NAME := {format | border | expanded | fieldsep | footer | null | numericlocale | recordsep | tuples_only | title | tableattr | pager})
`\t [on|off]` show only rows
`\T [STRING]` set HTML <table> tag attributes, or unset if none
`\x [on|off]` toggle expanded output

Connection

`\c[onnect] [DBNAME | - USER | - HOST | - PORT | -]` connect to new database
`\encoding [ENCODING]` show or set client encoding
`\password [USERNAME]` securely change the password for a user
`\conninfo` display information about current connection

Variables

`\prompt [TEXT] NAME` prompt user to set internal variable
`\set [NAME [VALUE]]` set internal variable, or list all if no parameters
`\unset NAME` unset (delete) internal variable

Informational

(options: S = show system objects, + = additional detail)
`\d[S+]` list tables, views, and sequences
`\d[S+] NAME` describe table, view, sequence, or index
`\da[S] [PATTERN]` list aggregates
`\db[+] [PATTERN]` list tablespaces
`\dc[S] [PATTERN]` list conversions
`\dC [PATTERN]` list casts
`\dd[S] [PATTERN]` show comments on objects
`\ddp [PATTERN]` list default privileges
`\dD[S] [PATTERN]` list domains
`\des[+] [PATTERN]` list foreign servers
`\deu[+] [PATTERN]` list user mappings
`\dew[+] [PATTERN]` list foreign-data wrappers
`\df[antw][S+] [PATTERN]` list [only agg/normal/trigger/window] functions
`\dF[+] [PATTERN]` list text search configurations
`\dFd[+] [PATTERN]` list text search dictionaries
`\dFp[+] [PATTERN]` list text search parsers
`\dg[+] [PATTERN]` list roles (groups)
`\dFt[+] [PATTERN]` list text search templates
`\di[S+] [PATTERN]` list indexes
`\dl` list large objects, same as `\lo_list`
`\do[S] [PATTERN]` list operators
`\dp [PATTERN]` list table, view, and sequence access privileges
`\dr[S+] [PATTERN]` list foreign tables
`\drds [PATTERN1 [PATTERN2]]` list per-database role settings
`\ds[S+] [PATTERN]` list sequences
`\dt[S+] [PATTERN]` list tables
`\dT[S+] [PATTERN]` list data types
`\du[+] [PATTERN]` list roles (users)
`\dv[S+] [PATTERN]` list views
`\dx [PATTERN]` list external tables
`\l[+]` list all databases
`\z [PATTERN]` same as `\dp`

Operating System

`\cd [DIR]` change the current working directory
`\timing [on|off]` toggle timing of commands
`\! [COMMAND]` execute command in shell or start interactive shell

Large Objects

`\lo_export LOBOID FILE` Large Object Operations
`\lo_import FILE [COMMENT]`
`\lo_list`
`\lo_unlink LOBOID`